



The new Cam Set Torque Anchor is a cam-style torque anchor that uses an anchor/drag block combination.


The Cam Set Torque Anchor's design ensures that regardless of the torque load from the pump, the anchor blocks will continue to engage the casing without slipping. The higher the torque load on the Cam Set Torque Anchor, the harder the anchor blocks will bite the casing.

The proven success and reliability of the cam design has been implemented in a variety of torque anchors. The Cam Set Torque Anchor is a reliable torque anchor that will provide secure pump placement.

The Cam Set Torque Anchor is available for all casing sizes with a variety of connection sizes and types.


Casing Size		Torque Anchor Body OD		Torque Anchor ID		Connections*	
Inch	mm	Inch	mm	Inch	mm	inch	mm
4 ½"	114.3	3.61"	91.7	1.995"	50.7	2 3/8" EU	60.3
5 ½"	139.7	3.61"	91.7	1.995"	50.7	2 3/8" EU	60.3
5 ½"	139.7	4.50"	114.3	2.441"	62.0	2 7/8" EU	73.0
5 ¾"	146.1	4.50"	114.3	2.441"	62.0	2 7/8" EU	73.0
6 5/8"	168.3	4.50"	114.3	2.441"	62.0	2 7/8" EU	73.0
7"	177.8	4.50"	114.3	2.441"	62.0	2 7/8" EU	73.0
7"	177.8	5.70"	144.8	2.992"	76.0	3 ½" EU	88.9
8 5/8"	219.1	5.70"	144.8	2.992"	76.0	3 ½" EU	88.9
9 5/8"	244.5	5.70"	144.8	2.992"	76.0	3 ½" EU	88.9

Alternative connections and specially engineered sizes are available upon request



Run In

The 3 anchor blocks (red) are in the lowest point of the cams on the mandrel to allow running the tool downhole



Set Position

When torque is applied, the anchor blocks (red) move along the cams on the mandrel. The more torque applied, the stronger the anchor blocks bite the casing.



Suite 245, 6025 - 12th Street S.E., Calgary, Alberta, Canada T2H 2K1

Tel. # (403)-543-0350, Fax. # (403)-543-0351

canam@canamservices.com www.canamservices.com