



PUMP		STATOR						ROTOR			
PC Pump Series		Displacement Bbl/Day/ 100 RPM	Top Connection EUE (IN)	Length	Max O.D.	Tag Bar Distance	Weight	Top Connection API Pin	Length	Max O.D.	Weight
Metric	Imperial			IN.	IN.	IN.	Lbs.	IN.	IN.	IN.	Lbs.
4-1200	25-4100	25	2 7/8 Pin	95	3.1	6	80	3/4 Pin	103	1.368	24
4-1800	25-6000	25		142		6	120		150		33
10-1200	60-4100	60	2 7/8 Box	131	3.5	17	139	7/8 Pin	146	1.677	53
10-1500	60-5000	60	Or	163		17	174		178		66
10-1800	60-6000	60	3 1/2 Box	197		17	209		212		77
10-2400	60-8000	60		262		17	278		277		106
15-1400	95-4600	95	2 7/8 Box	172	3.5	17	190	7/8 Pin	187	1.925	68
15-1800	95-6000	95	Or	215		17	245		231		88
15-2000	95-6600	95	3 1/2 Box	237		17	270		253		98
16-1200	100-4100	100	2 7/8 Box	158	3.5	17	167	7/8 Pin	174	1.945	62
16-1500	100-5000	100	Or	197		17	208		211		78
16-1800	100-6000	100	3 1/2 Box	237		17	250		252		90
16-2400	100-8000	100		316		17	334		332		124
24-1200	150-4100	150	2 7/8 Box	211	3.5	17	222	7/8 Pin	225	1.825	83
24-1500	150-5000	150	Or	263		17	278		277		78
24-1800	150-6000	150	3 1/2 Box	316		17	334		330		90
32-900	200-3100	200	3 1/2 Box	161	4.5	17	260	1" Pin	177	2.272	108
32-1200	200-4100	200		214		17	347		230		141
32-1500	200-5000	200		269		17	433		284		180
32-1800	200-6000	200		322		17	520		338		207
44-1400	280-4600	280	3 1/2 Box	252	4.5	17	520	1" Pin	265	2.2	207
44-1800	280-6000	280		303		17	650		317		266
44-2100	280-6900	280		379		17	780		394		326
54-900	340-3100	340	3 1/2 Box	242	4.5	17	260	1" Pin	257	2.272	108
54-1200	340-4100	340		322		17	520		338		213
54-1500	340-5000	340		403		17	650		418		266
54-1800	340-6000	340		484		17	780		499		326
64-800	400-2700	400	3 1/2 Box	242	4.5	17	488	1" Pin	257	2.259	160
64-1040	400-3500	400		322		17	650		338		213
64-1300	400-4400	400		403		17	813		418		266
64-1560	400-5350	400		484		17	975		499		320
96-800	600-2700	600	3 1/2 Box	289	4.5	17	535	1" Pin	278	2.286	176
96-1040	600-3500	600	X 2" Weld Ext.	378		17	713		367		235
96-1300	600-4400	600		466		17	891		455		294
98-1580	615-5200	615	4 1/2 Box	350	5.5	26	945	2 3/8 PAC Pin	372	2.965	320
110-800	690-2700	690	4 1/2 Box	175	5.5	26			192		161
110-1200	690-4100	690	4 1/2 Box	262	5.5	26	26473	2 3/8 Pin	282	2.97	240
110-1600	690-5300	690	5 1/2 LTC	350		26	946	PAC	377		321
150-600	940-2000	940	3 1/2 Box	378	4.5	17	713	1" Pin	367	2.264	235
150-750	940-3500	940	X 2" Weld Ext.	466		17	891		455		293
150-900	940-3100	940		555		17	1070		544		353
165-1800	1030-6000	1030	6 5/8 Buttress Pin	402	6.6	26	N/A	27/8 PAC Pin	428	3.99	N/A