

**SQUARE KELLY STD DIMENSIONS**

NOMINAL KELLY SIZE OD		STD LENGTHS		TOP LH THREAD CONNECTION	TOP CONNECTION OD		BOTTOM RH CONNECTION THREAD	BOTTOM CONNECTION OD		STD BORE		APPROX WEIGHT PER 40 FT SECTION	
IN	MM	FT	M		IN	MM		IN	MM	IN	MM	LB	KG
3 1/2	88.9	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC38 (3 _" API IF)	4 3/4	120.65	2 1/4	57.15	1320	600
		42	12.8										
		46	14.02										
3 1/2	88.9	40	12.19	4 _" API REG LH	5 3/4	146.04	NC38 (3 _" API IF)	4 3/4	120.65	2 1/4	57.15	1320	600
		42	12.8										
		46	14.02										
4 1/4	107.95	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC46 (4" IF)	6 - 6 3/6	125.40 - 161.92	2 13/16	71.37	1820	827.27
		42	12.8										
		46	14.02										
4 1/4	107.95	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC50 ( 4 _" IF)	6 1/8- 6 3/8	155.57-161.92	2 13/16	71.37	1820	827.27
		42	12.8										
		46	14.02										
5 1/4	133.35	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC56 OR 5 _" FH	7	177.8	3	76.2	2780	1263.63
		42	12.8										
		46	14.02										
6	152.4	40	12.19	6 5/8" API REG LH	7 3/4	196.85	6 5/8" API REG	7 3/4	196.85	3	76.2	3700	1681.81
		42	12.8										
		46	14.02										

**HEXAGONAL KELLY STD DIMENSIONS**

NOMINAL KELLY SIZE OD		STD LENGTHS		TOP LH THREAD CONNECTION	TOP CONNECTION OD		BOTTOM RH CONNECTION	BOTTOM CONNECTION OD		STD BORE		APPROX WEIGHT PER 40 FT SECTION	
IN	MM	FT	M		IN	MM		IN	MM	IN	MM	LB	KG
3 1/2	88.9	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC31 (2 7/8" API IF)	4 1/8	104.77	1 3/4	44.45	1300	590.9
		42	12.8										
		46	14.02										
3 1/2	88.9	40	12.19	4 _" API REG LH	5 3/4	146.04	NC31 (2 7/8" API IF)	4 1/8	104.77	1 3/4	44.45	1200	545.45
		42	12.8										
		46	14.02										
4 1/4	107.95	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC38 (3 _" IF)	4 3/4	120.65	2 1/4	57.15	1740	790.9
		42	12.8										
		46	14.02										
5 1/4	133.35	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC46 (4" IF)	6 - 6 3/8	125.40 - 161.92	2 13/16	71.37	2550	1159.09
		42	12.8										
		46	14.02										
5 1/4	133.35	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC50 ( 4 _" IF)	6 1/8 - 6 3/8	155.57-161.92	3	76.2	2550	1159.09
		42	12.8										
		46	14.02										
6	152.4	40	12.19	6 5/8" API REG LH	7 3/4	196.85	NC56 OR 5 _" FH	7	177.8	3	76.2	3040	1381.81
		42	12.8										
		46	14.02										