















ROTARY SHOES AVAILABLE

	<p align="center">TYPE A</p> <p>This shoe is used to size and dress the top of the fish inside the casing. It makes a tapered cut on the fish without damaging the casing and cuts on the damaging the casing and cuts on the I.D., O.D and the bottom.</p>		<p align="center">TYPE H</p> <p>Is a drag type shoe used to cut soft formation, or when running weak string. It cuts on the bottom only.</p>
	<p align="center">TYPE B</p> <p>Is used in open hole for washing over and cutting formation, metal or cement with limited inside clearance. It cuts on the I.D., O.D. and the bottom</p>		<p align="center">TYPE I</p> <p>Is a low torque type shoe used inside casing to wash over and cut on the bottom only to avoid damage to the casing or fish.</p>
	<p align="center">TYPE C</p> <p>Is used to cut metal on the fish with no damage to the casing. It cuts on the I.D and the bottom.</p>		<p align="center">TYPE J</p> <p>Is used to cut metal on the fish without damaging the casing. It cuts the bottom and on the I.D. only.</p>
	<p align="center">TYPE D</p> <p>Is used for washing over and cutting formation only. It cuts on the O.D. and the bottom only.</p>		<p align="center">TYPE K</p> <p>Is used in open hole for washing over and cutting metal and metal and cement with limited inside clearances. It cuts on the bottom and O.D.</p>
	<p align="center">TYPE E</p> <p>Is used for washing over and cutting formation only. It cuts on the bottom, but not on the I.D and O.D.</p>		<p align="center">TYPE L</p> <p>Is used for washing over and cutting metal formation, or cement. It cuts freely on the I.D., and O.D. and bottom.</p>
	<p align="center">TYPE F</p> <p>Is used inside casing for washing over and cutting on the bottom only. It does not cut on the I.D. or the O.D.</p>		<p align="center">TYPE M</p> <p>It cuts metal on the fish without damaging the casing because it does not cut on the O.D. It cuts on the I.D. and the bottom only.</p>
	<p align="center">TYPE G</p> <p>Is a low torque type shoe used for cutting metal, formation, or cement on open hole. It cuts freely on the I.D., O.D. and the bottom.</p>		<p align="center">TYPE N</p> <p>Is used in open hole with limited outside clearance to cut metal or cement and a limited amount of formation without damaging the fish. It cuts on O.D. and bottom only.</p>