



СТАНДАРТНЫЕ НАСОСЫ

МОДЕЛЬ	Расход при 100 об/мин (м³/сут)	Суммарная высота подъёма (м)	КАНАМ НОМЕР	Резьба муфты (мм-API)	Резьба ротора (мм-API штанги)	Общая длина (см)
7-700	7	700	7700EP	73 PIN	22	203
7-1400	7	1400	71400EP			399
7-1800	7	1800	71800EP			528
7-2200	7	2200	72200EP			615
10-600	10	600	10600EP	73 or 89 BOX	22	203
10-1200	10	1200	101200EP			406
10-1600	10	1600	101600EP			487
10-1800	10	1800	101800EP			541
10-2400	10	2400	102400EP			742
15-700	15	700	15700EP	73 or 89 BOX	22	211
15-1000	15	1000	151000EP			361
15-1400	15	1400	151400EP			495
15-1800	15	1800	151800EP			630
15-2200	15	2200	152200EP			734
27-600	27	600	27600EP	89MM BOX	25	262
27-1200	27	1200	271200EP			526
27-1500	27	1500	271500EP			643
27-1800	27	1800	271800EP			754
32-600	32	600	32600EP	89MM BOX	22	356
32-900	32	900	32900EP			584
32-1200	32	1200	321200EP			754
32-1600	32	1600	321600EP			879
45-1000	45	1000	451000EP	89MM BOX	25	635
45-1200	45	1200	451200EP			765
45-1500	45	1500	451500EP			950
45-1800	45	1800	451800EP			1115



56-800	56	800	56800EP	89MM BOX	25	559
56-1000	56	1000	561000EP			739
56-1200	56	1200	561200EP			925
56-1500	56	1500	561500EP			1135
83-600	83	600	83600EP	89MM BOX	25	678
83-800	83	800	83800EP			922
83-1000	83	1000	831000EP			1107
83-1200	83	1200	831200EP			1351
105E-900	105	900	105E900EP	89MM BOX	25	932
105E-1200	105	1200	105E1200EP			1219
120-750	120	750	120750EP	89MM BOX	25	996
120-950	120	950	120950EP			1229
120-1150	120	1150	1201150EP			1473
140E-900	140	900	140E900EP	89MM BOX	25	1255
140E1200	140	1200	140E1200EP			1478